




PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : H04B 1/16, 1/38, H04Q 7/32	A1	(11) International Publication Number: WO 00/18025 (43) International Publication Date: 30 March 2000 (30.03.00)
(21) International Application Number: PCT/EP99/07721 (22) International Filing Date: 13 September 1999 (13.09.99) (30) Priority Data: 9820212.0 17 September 1998 (17.09.98) GB (71) Applicant (for all designated States except US): NOKIA MOBILE PHONES LIMITED [FI/FI]; Keilalahdentie 4, FIN-02150 Espoo (FI). (72) Inventors; and (75) Inventors/Applicants (for US only): KERAI, Kanji [GB/GB]; 1 Boycroft Avenue, Kingsbury, London NW9 8AH (GB). SCALES, James [GB/GB]; Cadomin, Wards Cross, Hurst, Wokingham, Berks (GB).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the</i> <i>claims and to be republished in the event of the receipt of</i> <i>amendments.</i>

(54) Title: PORTABLE COMMUNICATION TERMINAL**(57) Abstract**

A portable communication terminal comprising a user interface, a radio transceiver for communicating with a telecommunication network and a low power radio frequency (RF) transceiver by which a low power radio frequency (RF) communication link can be established with a local terminal, wherein, in response to a user input via the user interface, the portable terminal monitors signals received by the low power radio frequency (RF) transceiver with a view to establishing the low power radio frequency (RF) link.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

PORTABLE COMMUNICATION TERMINAL

The present invention relates to a portable communication terminal.

5

As technology advances, it is becoming more and more usual for devices to communicate with each other. For instance, a radiotelephone may act as a gateway to the public telephone switching network (PTSN) for a local data terminal such as, for example, a PC, a laptop PC, a personal organiser, a
10 smart phone, a personal digital assistant (PDA), a printer, a facsimile machine and the like. Interfacing between the such devices may be accomplished via a low power radio frequency (RF) link. Such interfaces may be provided between almost any digital device e.g. computers, phones, scanners, cameras, headsets, keyboards, joysticks etc.

15

Such low power radio frequency links are the focus of the "Bluetooth" initiative of major telecommunications players launched in May 1998. Further discussion of this initiative can be found on pages 26-27 of "Mobile Communications International" September 1998. On the road, this
20 technology would allow notebook users to use a smart phone as a modem to dial in to a corporate network. Within an office, the technology could be used in network hubs to keep users connected to the network as they move about the corporation. It would also allow users to synchronise personal data, such as an address book, between a PDA and a PC.

25

Low power radio frequency (RF) transmission envisages a power of the order of 1mW (or 0 dB) for operation over distances in the range of 10cm to 30 meters. Currents of around 8 to 30mA at a voltage around 2.7V are contemplated. Data rates of around 1Mbps are envisaged for communication
30 between devices such as hand-held computers, notebooks and cellular

phones. The frequency used in such scenarios is envisaged to be around 2.4 GHz.

5 The present invention has particular, but not exclusive, application to the management of the low power radio frequency (RF) link in the above and similar circumstances.

10 With this in mind, in one aspect the present invention provides a terminal comprising a user interface, a radio transceiver for communicating with a telecommunication network, and a low power radio frequency (RF) transceiver by which a low power radio frequency (RF) communication link can be established with a local terminal, wherein, in response to a user input via the user interface, the terminal monitors signals received by the low power radio frequency (RF) transceiver with a view to establishing the low power radio frequency (RF) link.

15 By limiting the occasions when the portable communication terminal seeks to establish the low power radio frequency (RF) link only to those occasions when a user input indicates that the user is requesting that the low power radio frequency (RF) link is established, power savings resulting from reduced use of the low power radio frequency (RF) transceiver can be achieved.

20 Preferably, if no low power radio frequency (RF) link is established within a predetermined interval, for example 20 seconds, the monitoring activity of the low power radio frequency (RF) transceiver is discontinued. By limiting the monitoring activity in this way, further power savings can be achieved in circumstances where for some reason it has not been possible to establish the low power radio frequency (RF) link within a reasonable period.

In another aspect, the present invention provides a method of communicating between two terminals via a low power radio frequency (RF) link in which at least one of the terminals monitors for low power radio frequency (RF) activity in response to a user input via its user interface.

5

In a further aspect, the present invention provides a terminal comprising a user interface and a low power radio frequency (RF) transceiver by which a low power radio frequency (RF) communication link can be established with a local terminal, wherein, in response to a user input via the user interface, the terminal monitors signals received by the low power radio frequency (RF) transceiver with a view to establishing the low power radio frequency (RF) link.

Exemplary embodiments of the invention are hereinafter described with reference to the accompanying drawings, in which:

15

Figure 1 shows a perspective view of a terminal according to the invention;

Figure 2 shows a diagram of the main features in the terminal of Figure 1; and

20

Figure 3 shows a diagram of the terminal of Figure 1 establishing a low power radio frequency (RF) link with a PC.

The terminal shown in Figure 1 is a cellular mobile telephone 1 having an 'A' or front cover 3a and a 'B' or rear cover 3b powered by a rechargeable battery pack 2. The user interface of the telephone 1 comprises a liquid crystal display 5 having backlighting, a microphone 7, a loudspeaker 8 and a keypad 6. The keypad 6 comprises two groups of keys: a first group of alphanumeric keys 6a for entering telephone numbers and text data, and a second group of

25

functions keys 6b for enabling/disabling functions of the telephone 1 or causing operations of the telephone 1 to be executed.

Referring to Figure 2, the telephone includes a transceiver 9 for transmitting and receiving signals to and from a cellular telecommunication network. A controller 4 in the form of a microprocessor controls the operation of the telephone 1 including its user-interface, a memory 14, the radio transceiver 9 and a low power radio frequency (RF) transceiver 16 (not visible in the Figure 1 view).

10

One of the function keys 66, the ON/OFF key, can be depressed for a relatively long duration (>1 second) to cause the controller 4 to switch the telephone 1 between an off mode in which negligible battery power is consumed to an on mode. In an on mode, the telephone 1 can be considered to be in any one of a call processing mode, an active standby mode or a passive standby mode.

15

In the call processing mode, a telephone call is conducted over the (radio) air interface via the radio transceiver 9. Due to heavy use of the air interface during calls, this mode results in high power consumption.

20

In active standby mode, power is consumed as a result of certain user-interface functions of the telephone 1 and the radio transceiver 9. In passive standby mode, power is consumed substantially only as a result of the radio transceiver 9. In either kind of standby mode, the power consumption of the radio transceiver 9 arises out of the need to access the air interface to maintain registration with the cellular network, specifically, for example, to watch for incoming calls and hand over from one cell to another as the telephone 1 changes location, even though no calls traffic is being processed.

25

The difference between the two standby modes lies in the fact that in active

30

standby mode, the user is able to make use of the keypad 6 and the display 5 in order to review or alter the contents of the memory 14, for example, with a view to adding a number to the telephone number store or altering a control setting of the telephone 1. In this active standby mode, the backlighting of the display 5 is activated. In order to move between the active standby mode and the passive standby mode, the keys MENU and * are pressed sequentially. In passive standby mode, the display 5 and its backlighting are inactive as is the keypad (except, of course, in response to the sequential pressing of the MENU and * keys). While in passive standby mode, if an incoming call is received, then depression of any key accepts the call and thus the telephone 1 enters the call processing mode.

Figure 3 shows the telephone 1 and a local data terminal in the form of a PC 50. The PC comprises a keyboard 52, a cathode ray visual display 54 and a low power radio frequency (RF) transceiver 18. In order to send a facsimile document prepared on the PC 50 using the telephone 1 as a gateway to the PTSN, the data defining the facsimile needs to be transferred to the telephone 1 via their respective low power radio frequency (RF) transceivers 16, 18.

The PC 50 and the telephone 1 are arranged such that their low power radio frequency (RF) transceivers 16, 18 are in range of each other. Initially, the telephone 1 is in passive standby mode. On sequentially pressing the MENU and * keys, the telephone 1 switches from passive standby mode to active standby mode. Also, the low power radio frequency (RF) transceiver 16 of the telephone 1 starts to monitor or poll for incoming low power radio frequency (RF) signals with a view to establishing a low power radio frequency (RF) link (20) between the telephone 1 and the PC 50. If during a 20 second period, the PC 50 transmits signals which seek to create a low power radio frequency (RF) link, then a low power radio frequency (RF) link is established permitting the facsimile document data to be transmitted. If, however, after the 20

second period, no link is established then the telephone 1 discontinues monitoring the incoming low power radio frequency (RF) signals. It will thus be appreciated that the functional effect of sequentially pressing the MENU and * keys is two fold, firstly, to switch the telephone 1 from passive standby
5 to active standby mode, but also secondly to start the monitoring activity.

In other embodiments, the user input for the low power radio frequency (RF) transceiver 16 to start to monitor low power radio frequency (RF) activity can be actions which are dedicated to or have the sole functional effect of
10 triggering the monitoring activity. Examples include the selection of an option from a menu, the depression of predetermined keys, either in a defined sequential order or simultaneously, or a voice command.

When the low power radio frequency (RF) transceiver 16 is not polling for low
15 power radio frequency (RF) activity, it can be either 'on' but not consuming much power by virtue of not actively polling for low power radio frequency (RF) activity, or shut-down into a power-saving or standby mode where it uses negligible power.

20 In another embodiment, when the telephone 1 is in the off mode, the trigger to start monitoring low power radio frequency (RF) activity can be provided by depression of the ON/OFF key for a relatively short duration which is insufficient to place the telephone 1 into on mode. If during the 20 second interval, no low power radio frequency (RF) link is established then the
25 monitoring activity is discontinued and the telephone 1 remains in off mode. On the other hand, if a low power radio frequency (RF) link is established, then the telephone 1 is switched to the on mode.

The terminal has been described with reference to a radiotelephone however the invention has application to many other devices e.g. printers etc. as set out in the initial paragraphs of this document.

CLAIMS

1. A portable communication terminal, comprising:
a user interface;
5 a radio transceiver for communicating with a telecommunication network;
and
a low power radio frequency (RF) transceiver by which a low power radio
frequency (RF) communication link can be established with a local
terminal;
10 wherein, in response to a user input via the user interface, the terminal
monitors signals received by the low power radio frequency (RF)
transceiver with a view to establishing the low power radio frequency
(RF) link.
- 15 2. A portable communication terminal as in Claim 1, wherein, if no low
power radio frequency (RF) link is established within a predetermined
interval, said monitoring is discontinued.
- 20 3. A portable communication terminal as in Claims 1 or 2, wherein the user
input comprises the depression of predetermined keys.
4. A portable communication terminal as in any of Claims 1 to 3, wherein
the user input comprises a voice command.
- 25 5. A portable communication terminal as in Claims 3 or 4, wherein the user
input has the sole functional effect of triggering said monitoring.
6. A portable communication terminal as in Claims 3 or 4, wherein the user
input has the functional effect of triggering said monitoring and changing
30 the mode of operation of the portable terminal.

7. A terminal comprising a user interface and a low power radio frequency (RF) transceiver by which a low power radio frequency (RF) communication link can be established with a local terminal, wherein, in response to a user input via the user interface, the terminal monitors signals received by the low power radio frequency (RF) transceiver with a view to establishing the low power radio frequency (RF) link.
8. A portable communication terminal constructed, arranged and adapted to operate substantially as hereindescribed with reference to the accompanying drawings.




FIG. 1




FIG. 2




FIG. 3

INTERNATIONAL SEARCH REPORT

Internat. Application No

PCT/EP 99/07721

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 H04B1/16 H04B1/38 H04Q7/32

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04B H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X A	EP 0 821 502 A (NOKIA MOBILE PHONES LTD) 28 January 1998 (1998-01-28) abstract page 1, line 1 - line 12 page 5, line 44 - line 58 page 11, line 11 -page 13, line 35 ---	8 1-3,5-7
P,X A	WO 99 16280 A (ERICSSON GE MOBILE INC) 1 April 1999 (1999-04-01) abstract page 4, line 3 -page 10, line 29 figure 2 --- -/--	8 1-3,5-7

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

10 January 2000

Date of mailing of the international search report

17/01/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Lindhardt, U

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 99/07721

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	HAARTSEN J: "BLUETOOTH - THE UNIVERSAL RADIO INTERFACE FOR AD HOC, WIRELESS CONNECTIVITY" ERICSSON REVIEW, SE, ERICSSON. STOCKHOLM, no. 3, 1 January 1998 (1998-01-01), page 110-117 XP000783249 ISSN: 0014-0171	8
A	the whole document -----	1,7

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 99/07721

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0821502 A	28-01-1998	JP 10117184 A	06-05-1998
WO 9916280 A	01-04-1999	AU 9297698 A	12-04-1999